

SIGNA UNO 36

MODEL NUMBER

SIGNA UNO 36

SPECIFICATIONS

HOUSING : Cold roll steel 0.8mm.

LIGHT SOURCE : The fitting is designed to operate a 33W LED.

LENS : Dark Light low glare

MOUNTING : Ceiling mounted recessed or suspended.

COLOUR CONSISTENCY : Mac Adams 3 SDCM.

LUMEN MAINTENANCE : L80B50.

LIGHT EFFICIENCY : 121.09 lm/W

CCT : 4000K.

UGR : <16.

CRI : 90.

DIMENSIONS : 595mm x 595mm x 40mm.

CUT OUT : 570mm x 570mm.

APPLICATION : Suitable for indoor use only.

Operating Temperature (Ta) - 20° C to +30° C.

FEATURES : Dimmable and Emergency option available on request.



APPLICATION AREAS

Indoor application.
Commercial Developments.
Retail Developments.
Shopping malls.
Public buildings.



COLOURS

☐ White (W)

LIGHT SOURCE

LED

LED CURRENT (mA)	SYSTEM WATTAGE (W)	COLOUR TEMP (K)	LUMINOUS FLUX (lm)
700mA	26W	4000K	3149 lm
800mA	30W		3598 lm
900mA	33W		4048 lm

EMERGENCY LIGHTING (OPTIONAL)

PACK 1 - REMOTE EMERGENCY 20W-60W

DURATION	BACK-UP LIGHT OUTPUT	BATTERY TYPE	INTEGRATION	SELF-TESTING	DIMENSIONS
3 HOURS	20%	Lithium-ion	Remote	Yes	212x73x28mm


REMOTE EMERGENCY PACK

Lithium iron phosphate battery
Test switch & LED charge indicator with holder
Charge time : 16 hours

LED INDICATOR HOLDER

HOLE CUT OUT

 20mm Ø.




LED INDICATOR

	Green stable: battery charging and fully charged
	Green off, DC mode (battery operation, emergency mode)


DIMENSIONS IN MM

HOLE CUT OUT

 570mm x 570mm



Bottom View



Side View

LIGHT DISTRIBUTION

LED 26W

