

STELLA 125

MODEL NUMBER

STELLA 125

SPECIFICATIONS

HOUSING : Die cast and extruded aluminium.

HEAT SINK : Thermally engineered aluminium extrusion.

DIFFUSER : High Transparency PC cover. The surface frosted soft light technology is used to treat multiple layers of anti glare apertures, effectively preventing glare.

LIGHT SOURCE : The fitting is designed to operate a 24W LED.

REFLECTOR : Matt white.

FINISH : Powder coated.

MOUNTING : Ceiling mounted recessed.

COLOUR CONSISTENCY : Mac Adams 3 SDCM

SIZE : 133mm Ø x 80mm.

CUT-OUT : 125mm Ø

CCT : 3000K, 3500K or 4000K . Settable.

CRI : 90.

IP RATING : IP44.

APPLICATION : Suitable for indoor use only.

OPERATING TEMPERATURE : (Ta) - 20° C to +30° C.

Fitting supplied with external power supply.

DIMMING : On/Off.



LIGHT SOURCE

LED

LUMINAIRE WATTAGE (W)	COLOUR TEMP (K)	LUMINOUS FLUX (lm)
24W	3000K	2613 lm
	3500K	2855 lm
	4000K	2724 lm

APPLICATION AREAS

Indoor application.
Symmetrical distribution.
Commercial developments.
Retail developments.
Shopping malls.
Public buildings.




DIMENSIONS IN MM


HOLE CUT OUT



125mm Ø



Bottom View



Side View

LIGHT DISTRIBUTION

55° Beam

